

DO NOT EXPOSE TO UN MAT



ATTHAS FILL TO BE

With silver-based antimicrobial additives



AIM post filter: re-mineralizer



AIC post filter: remove bad odours and tastes





SIP A BETTER WATER!

Under-sink reverse osmosis systems with built-in silver-based antimicrobial protection.





mod. STANDARD

Under-sink reverse osmosis

OASIS SANIC is a range of under-sink reverse osmosis systems that are equipped with built-in silver-based antimicrobial protection, designed to provide complete water treatment directly from the home faucet.

Proper use of the system can significantly reduce the levels of most water pollutants, such as pesticides, nitrates, fertilizers, heavy metals, and pathogenic microorganisms, while also enhancing the taste and flavour of the water.

The use of OASIS SANIC systems also helps reduce the consumption of bottled water, thus contributing to a cleaner environment with less waste.

mod. PUMP

units major features

- Shut-off valve (STD and UV models)
- Solenoid valve (PUMP and PUMP-UV models)
- High pressure pump (PUMP and PUMP-UV models)
- Pressure gauge (F models with frame)
- AC plug 2 pins C type CEE 7/16 (Europlug)
- Min and Max pressure switch
- AIC activated carbon post-filter
- AIM re-mineralizer post-filter
- Installation kit with dedicated tap

benefits

- Antimicrobial technology thanks to the antibacterial properties of silver.
- The taste of water, foods, and beverages will be enhanced.
- Less pollution and more savings due to the drastic reduction of bottled water.
- Small and compact, OASIS SANIC fits most under-sink spaces.



<image>

 $\mathbf{mod.} \cup \vee$

mod. PUMP / UV

accessories included		
Dedicated storage tank	Dedicated tap	

-WORKING CONDITIONS



Max inlet pressureMin. inlet pressure8 bar (116 psi)3 bar (45.5 psi)Min. inlet pressure

1 bar (14.5 psi) (Pump models only)



•••

Max working temperature 45°C (113°F)



Membrane capacity **75**

capacity **75 GPD** (284 I/day)



mod. FRAME + PUMP



mod. FRAME + PUMP / UV

DIAPHRAGM BOOSTER PUMP

 (\rightarrow)

Supply power ß 220/230V - 50-60 Hz 4 Voltage 24 V Amperage **(A**) 0,9 A Power (4)

17 W

Open flow ₽ 1.34 I/min (0.35 GPM) Max output pressure psi

Flow at 5,5 bar (80 psi)

0.63 I/min (0.17 GPM)

8 bar (116 psi)

UV LAMP

- UV-C dose -00)-300 J/m²
- Supply power 220/230V - 50-60 Hz
- Voltage 24 V

- Amperage (A) 0.03 A
- Electrical absorption (4 6 W
- Lamp service life **(7**) 8000 hours



www.atlasfiltri.com



SANIC antimicrobial products feature proven Microban silver-based technology to protect against the growth and the reproduction of microorganisms, such as bacteria. SANIC antimicrobial products are protected against bacterial growth by up to 99.99% PROTECTION AGAINST BACTERIAL GROWTH

HOW ANTIMICROBIAL TECHNOLOGY WORKS:



ETERNAL EFFECTIVENESS Microban silver-based technology is permanently integrated into SANIC products and is active throughout their life cycle. Microban reduces the growth of bacteria on the product surface 24 hours a day, 7 days a week.



POWERED BY







IT'S MADE IN ITALY





www.atlasfiltri.com